



# PVC-Précontraint FERRARI® 502 F/R

## Précontraint FERRARI® 502

FERRARI 502 is an extremely durable and dimensionally stable PVC. Made from the highest quality polymers able to withstand the elements longer than average PVC's FERRARI 502 is an excellent choice for architectural sails, structures and marquees where durability is paramount.

- WIDTH
- WEIGHT
- BASE CLOTH
- SURFACE FINISH
- TEAR STRENGTH
- TENSILE STRENGTH
- ADHESION
- FABRICATION METHODS
- FIRE RETARDANT

- u 180cm
- u 590gsm
- u Polyester 1100 Decitex
- u Lacquer both sides
- u 25 / 20 daN
- u 250 / 250 daN/5cm
- u 9 daN/5cm
- u Hot Wedge, Hot Air & High Frequency Welding: Sewing: Adhesive
- u M2/NFP 92.503 - B1/DIN 4102 - M2/UNE 23727-90 – California State Fire Marshal – T19- NFPA 701 – BS 7837 – SP Full Scale Test – Method 2205 – (502 only: LP 7 – UBC 31-1) – AS 1530 - SIS650082 – CSE 3/77 CLASS 2 – SN 198 898
- u Ofpanz care label OF-1



### FABRIC CARE

