



PVC-Précontraint FERRARI® 502S F/R

Précontraint FERRARI® 502S

FERRARI 502S offers a new generation weldable PVDF known as Formula S. This new Formula S allows ease of fabrication with no need to etch the surface prior to welding. Formula S is a surface treatment (an alloy of fluorinated and acrylic resins) which allows for ease of maintenance over time. The membrane will look new for longer and be more aesthetically pleasing. FERRARI 502S is an excellent choice for architectural sails, structures and marquees where durability is paramount.

WIDTH	u 250cm
WEIGHT	u 590gsm
BASE CLOTH	u Polyester 1100 Decitex
SURFACE FINISH	u Formula S PVDF
TEAR STRENGTH	u 28 / 28 daN
TENSILE STRENGTH	u 280 / 280 daN/5 cm
ADHESION	u 10 daN/5 cm
U/V WARRANTY	u 5 Year
FABRICATION METHODS	u Hot Wedge, Hot Air & High Frequency Welding; Sewing; Adhesive
FIRE RETARDANT	u M2/NFP 92.503 - B1/DIN 4102 - M2/UNE 23727-90 – California State Fire Marshal - NFPA 701 – BS 7837 – SP Full Scale Test – Method 2205 – SIS650082
FABRIC CARE	u Ofpanz care label OF-1



WHITE

