

FLORIDA VINYL

TECHNICAL DATA SHEET

25th January 2023

| | | |
|---------------------------|--|----------------------------|
| WIDTH | 137cm | |
| TOP SKIN | 0.15mm | |
| THICKNESS | 0.9mm (Approx) | |
| ROLL LENGTH | 30m | |
| SURFACE COATING | PVC/Foam Expanded / ABL Anti Stain Lacquer Protection | |
| BASE CLOTH | 100% Polyester Knit | |
| ANTI MOULD | Anti-Mould inhibitors | ASTM G21 |
| U/V RESISTANCE | QUV 500hrs | ASTM G53 |
| TEAR WING STRENGTH | MD 3.5kg↑ CD 3.5kg↑ | CNS.9520-K6730 |
| TENSILE STRENGTH | MD 24kg↑ CD 12kg↑ | CNS.9520-K6730 |
| BURST STRENGTH | 10 kg↑/cm ² | CNS.2054 3011 |
| ABRASION | 50,000+ cycles (Wyzenbeek) 100,000+ cycles (Martindale) | ASTM D4157 AS 2001.2.25 |
| FLEXING | 5,000 cycles (25°C Pass) | CNS.7705K-6679 |
| FIRE RETARDENT | 4in/min↓ | MVSS-302/PASS |
| FABRIC CARE | OFPANZ Care Label OF-2 | |

0800 656 000