

# EXTERNAL SCREEN MESH

## TECHNICAL DATA SHEET

25th November 2024

<b>WIDTH</b>	300cm
<b>ROLL LENGTH</b>	30m
<b>NOMINAL WEIGHT</b>	514gsm +/- 5%
<b>THICKNESS</b>	0.74mm +/- 5%
<b>COMPOSITION</b>	30% Polyester + 70% PVC
<b>OPENESS FACTOR</b>	5%
<b>YARN COUNT</b>	36 x 36
<b>BREAKING STRENGTH WARP/WEFT</b>	2233/ 2231 N/5cm
<b>COLOUR FASTNESS</b>	Grade 8 (SGS)
<b>BACTERIA &amp; FUNGAL RESISTANCE</b>	ASTM G21, ASTM E-2180
<b>U/V WARRANTY</b>	10 year
<b>FIRE RETARDANT</b>	AS/NZS 1530.2 , California Fire Marshall Title 19, NFPA® 701-TM
<b>FABRICATION METHODS</b>	<b>CUTTING:</b> Cold Cut, Ultrasonic, Crush Cut or Laser. <b>SEAMING/HEMMING:</b> Thermal, High Frequency, Hot Air or Sewing
<b>FABRIC CARE &amp; CLEANING</b>	Remove dust with vacuum cleaner or compressed air. Do not Scrub. Do not use solvents or and abrasive substance which might damage the coating on the fabric. Clean with a sponge or soft brush dipped in soapy water using a mild detergent. Rinse with clean water. Leave blind down until completely dry.