

OUTDOOR SCREEN MESH

TECHNICAL DATA SHEET

25th November 2024

WIDTH	300cm
ROLL LENGTH	30m
NOMINAL WEIGHT	514gsm +/- 5%
THICKNESS	0.74mm +/- 5%
COMPOSITION	30% Polyester + 70% PVC
OPENESS FACTOR	5%
YARN COUNT	36 x 36
BREAKING STRENGTH WARP/WEFT	2233/ 2231 N/5cm
COLOUR FASTNESS	Grade 8 (SGS)
BACTERIA & FUNGAL RESISTANCE	ASTM G21, ASTM E-2180
U/V WARRANTY	10 year
FIRE RETARDANT	AS/NZS 1530.2 , California Fire Marshall Title 19, NFPA® 701-TM
FABRICATION METHODS	CUTTING: Cold Cut, Ultrasonic, Crush Cut or Laser. SEAMING/HEMMING: Thermal, High Frequency, Hot Air or Sewing
FABRIC CARE & CLEANING	Remove dust with vacuum cleaner or compressed air. Do not Scrub. Do not use solvents or and abrasive substance which might damage the coating on the fabric. Clean with a sponge or soft brush dipped in soapy water using a mild detergent. Rinse with clean water. Leave blind down until completely dry.